

ECL-SP300 Mini Color Pan Tilt Zoom Dome


Fully Integrated Indoor Enclosures with Camera and Zoom Lens



Indoor



Outdoor



Pick Up Device	1/4" Sony DSP CCD
Resolution	470 TV Lines
Minimum Illumination	0.7 Lux
Lens	4.1 - 73.8mm Auto Focus (F1.4 - F3.0)
Zoom	10X Optical, 12X Digital (216X Total)
Infra-Red Sensitivity	None
Vertical Sync	Internal
Gain Control	Electronic Shutter 1/1 - 1/10,000sec. (22 steps)
White Balance	Auto, ATW, Indoor, Outdoor, One Push, Manual

Horizontal Rotation	(Pan Travel) 360° Continuous
Vertical Rotation	(Tilt Travel) 0° - 90° (Auto Flip)
Protocols	(RS-485) Pelco, Pelco-D, Pelco-P, Eclipse, Ultrak
Speed	70° Per Second
Speed Control	Variable (Adjusts to Manipulation)
Presets	64 Programmable
Touring (Auto Scan)	3 Tour Tracks / 2 Groups of 16 Programmable Preset Options
Smart Scan	2 Positions Preset (Adjustable Speed)
Focus Control	Manual / Auto (sensitivity adjustment normal or low)
Pan/Tilt Accuracy	+/- 0.05° Preset Recall
Upper Dome Material	Aluminum (IP66 for Outdoor Enclosure)
Lower Dome Material	Clear Acrylic (other options available)
Power Source	15VDC / 1000mA
Temperature	0 - 122F (-14 - 122F with Heater)
Humidity	10-75% RH Non Condensing

ECL-SP300 Mounting Bracket Options

Wall Mount (included) 	3" Pendant Mount (included) 	Recess Mount (sold separately) 
--	--	---

ECL-SP300 Part Numbers

ECL-SP300 Indoor Mini PTZ Dome	ECL-SP300E Outdoor Mini PTZ Dome
---	---