

MAX CCTV

MAX-PRO4 4-CAMERA DVR



- MONITOR OVER THE INTERNET USING IE BROWSER ●
- MPEG4 COMPRESSION FORMAT ●
- 4 VIDEO INPUTS, 1 AUDIO INPUT ●
- INTERNAL HARD DISK DRIVE ●
- USB PORT FOR BACKUP ●

FEATURES

MPEG4 Network Transmission - MPEG4 web transmitting for faster transmission and clearer images via network.

Simplex / Duplex Operation - Simplex/duplex selectable for live record, playback or backup and network operation.

Backup - Supports USB 2.0 flash drive backup.

Remote Surveillance - Up to 20 users simultaneously via licensed software AP and IE browser.

Intelligent Motion Trigger Recording - Advanced motion detection feature with 4 individually adjustable parameters.

Covert Recording - Blank screen replaces live monitor display to provide no indication that recording is taking place.

Individual Channel Quality Settings - Individual quality adjustments for each camera channel - Best, High, Normal and Basic quality.

A/V Support - 1 audio channel in, 1 audio channel out (mono).

Miscellaneous - Multi-language OSD, system auto-recovery after power failure, NTSC/PAL auto-detection, daylight savings time function, multiple network protocols (TCP/IP, PPPoE, DHCP and DDNS)

Storage & Hardware Specifications

HDDs: One (1) internal
HDD interface: IDE
HDD Quick Cleaning: Quick clean up of "index system" of recorded files - 750G under 2 seconds
External storage: USB interface on rear panel for backup
Network connection: LAN RJ45 on rear panel
Network protocols: TCP/IP, PPPOE, DHCP, DDNS
Ethernet: 10/100 Base-T, support remote control and live view
Compression: MPEG4
Video format: NTSC/PAL (auto-detect)
Video input: 4 BNC connectors
Video output: 1 BNC connector, composite 1Vp-p, 75 ohms
Audio input: 1 RCA connector
Audio output: 1 RCA connector (mono)
Power: 19VDC, <42 watts
Operating Temperature: 10°~40°C (50°~104°F)
Dimensions: 34.5(w)x6(h)x22.3cm(d) (13.6"x2.4"x8.8")

Video & On Screen Display (OSD) Specifications

Maximum Recording Rate (CIF): Simplex mode - 360x240 pixels w/120 IPS (NTSC), 360x288 pixels w/100 IPS (PAL) Duplex mode - 360x240 pixels w/40 IPS (NTSC), 360x288 pixels w/32 IPS (PAL)
Adjustable Recording Speed (CIF): Simplex mode - 120, 60, 30 IPS (NTSC), 100, 50, 25 IPS (PAL) Duplex mode - 40, 28, 20 IPS (NTSC), 32, 24, 16 IPS (PAL)
Image Quality Setting: Best / High / Normal / Basic
Remote Operation Software: Licensed software AP, IE browser (Windows 2000, XP, Vista compatible)
Recording Modes: Manual / Timer / Motion / Remote
Refresh Rate: 120 IPS (NTSC), 100 IPS (PAL)
Operation Modes: Simplex / Duplex selectable, Live Record / Playback / Backup / Network
Motion Detection Area: 16 x 12 grids per camera for all channels
Motion Detection Sensitivity: 4 adjustable variables with precise calculation for motion detection
Camera Title: Up to 6 letters.
Video Display Adjustments: Hue / Color / Contrast / Brightness
Date Display Format: YY/MM/DD, DD/MM/YY, MM/DD/YY, or OFF
Key Lock: YES
Video Loss Detection: YES
Multilingual OSD: YES